

**1** Dimensions: 23 5/8" (60 cm), 47 1/4" (120 cm). Components: topboard, baseboard. Thicknesses: 3 mm (3/32"), 4 mm (5/32"), 7 mm (9/32").

**2** Environmental conditions: 24h, 45%-65% humidity, 18°C (65°F). Prohibited: .

**3** Humidity: RH < 75%. \* sand cement screed 2%, \* wooden floor 10%, \* anhydrite 0,5%.

**4** Check for unevenness: 1 meter straightedge, max. 3 mm deviation.

**5** Apply Unifloor PE-foil 150 µm (4 mil) and Unifloor alutape. Dimensions: 1 15/16" (50 mm), 12", 200 mm.

**6** Prepare the base surface.

**7** Cut the base material.

**8** Lay the base material.

**9** Install side strip. Dimensions: 3/8", 10 mm.

**10** Lay the base material. Dimensions: 47 1/4" (120 cm), 30 cm, 11 13/13".

**11** Lay the base material. Dimensions: 47 1/4" (120 cm), 35 7/16" (90 cm), 30 cm, 11 13/13".

**12** Lay the base material. Dimensions: 35 7/16" (90 cm), 47 1/4" (120 cm), 11 13/13", 30 cm, 60 cm, 23 5/8".

**13** Lay the topboard. Dimensions: 47 1/4" (120 cm), 35 7/16" (90 cm), 23 5/8" (60 cm), 11 13/13", 30 cm. Board sizes: 30 x 90, 30 x 120, 60 x 120, 60 x 90.

**14** Lay the topboard. Prohibited: .

**15** Lay the topboard. Dimensions: 47 1/4" (120 cm), 23 5/8" (60 cm), 60 cm, 60 cm.

**16** Lay the topboard. Dimensions: 47 1/4" (120 cm), 23 5/8" (60 cm). Sequence: 1, 2, 3, 4. **Follow sequence!**

**17** Sand the topboard. Use 120 grain sand paper.

**18** Expansion joints. Dimensions: 33", max. 10 m, 5/8" (16 mm).

**19** Expansion joints between rooms. Dimension: 5/8" (16 mm).

**20** Lay the Heat-foil.

**21** Lay the Heat-blok. Use Unifloor PE-foil 200 µm (6 mil).

**22** Lay the Heat-blok. Dimensions: 3/8", 10 mm. Time: < 48h.

**Unifloor Underlay Systems**  
Arnsbergstraat 4  
7418 EZ Deventer - The Netherlands  
T +31 (0) 570 85 55 33  
E info@unifloor.nl

**UK Toll Free 0845 603 0 906**


**Service-Line für Deutschland, Österreich & Schweiz:**  
T +49 (152) 264 111 11



- ◆ Fast track subfloor preparation for when time is an issue
- ◆ Exceptionally stable free floating underlay system
- ◆ Superb smooth finish, ready for floor covering
- ◆ Instant floor levelling of most substrates
- ◆ Overcomes many substrate problems
- ◆ For the immediate glue-down of vinyl, linoleum, cork, rubber, carpet, etc.
- ◆ Quick and easy to fit and to handle (pack sizes)



FITTING INSTRUCTION FILM



**uniFloor**  
UNDERLAY SYSTEMS BV

Unifloor Underlay Systems  
Arnsbergstraat 4  
7418 EZ Deventer - The Netherlands  
T +31 (0) 570 85 55 33  
E info@unifloor.nl

UK Toll Free 0845 603 0 906

Service-Line für Deutschland,  
Österreich & Schweiz:  
T +49 (152) 264 111 11

[www.unifloor.nl](http://www.unifloor.nl)